

# TRIM TRIO CONTACTS

All three types of contacts mount on .150 inch centers for high density application. The TRIO has a flexible wire range accommodation from no. 26 thru no. 16 to subminiature coaxial or shielded cables. Each contact can be crimped with a variety of tools; hand, semi-, or fully-automatic, for prototype or high production. No insertion tool is necessary and one extraction tool will remove any of them.


The line consists of:

Subminiature coaxial  
male and female contacts



type RMDX/RCDX-2

no. 16 .0625 diameter machined  
pin and socket contacts



type RM/RC-M

No. 16 .0625 diameter strip fed formed  
pin and socket contacts



type SM/SC-M

The contacts are all made of high conductivity copper alloy. The standard plating is 30 microinches minimum gold over 200 microinches minimum silver which provides low contact resistance and good wear and corrosion protection. For other than standard plating, consult BURNDY for details.

**RETAINING SPRINGS** are made of tempered, heat-treated beryllium copper with bright nickel plating. The two spring locking legs provide high retention after numerous insertions and withdrawals. They are designed to withstand the unusual stresses imposed on them by leading wires off at sharp angles and by blind mating.

**INTERNAL SOCKET SPRING** totally enclosed in the no. 16 machined contact supplies high contact pressure between pin and socket to assure good electrical continuity and low contact resistance. It also provides a uniform engagement force between pin and socket, and will not take a set when probed.



SUBMINIATURE COAXIAL CONTACTS type RMDX/RCDX-2

The newly designed contacts for subminiature coaxial, shielded cables and twisted pair wires, consist of an inner pin/socket and outer male/female body. The insulating bushing in the body is made from thermoplastic and is designed to accept and permanently retain the inner contact. With this material the subminiature coaxial contact to can be used to an ambient temperature of 65°C. The tin plated, corrosion resistant outer ferrules not only hold the outer braid to the outer contacts, but also act as an insulation support to provide some insurance

against bending and vibration stresses on the cables.  
The HYFEN principle, as applied to subminiature and shielded cables, utilizes the crimp concept individually on the inner and the outer conductor enabling inspection of both critical crimp points.  
Subminiature coaxial contacts meet the applicable performance requirements of MIL-T-7928 and MIL-F-21608 for crimp type contacts, and MIL-E-16400 and MIL-I-983 for compression methods, and for grounding and terminating shields.

**Performance characteristics**  
Operating voltage between inner and outer contact 230 volts DC sea level working voltage.  
Test potential between inner and outer contact 500 volts AC 60 cycles for 1 minute.  
Operating temperature -27°C to +65°C (for higher operating temperatures, consult BURNDY).  
Contact retention in panel 15 pounds minimum.  
Contact voltage drop (maximum) 25 millivolts at 1 ampere for inner and outer contacts.  
Wire sizes other than those shown can also be accommodated. Consult BURNDY giving wire particulars.




Fig. 1 Fig. 2 Fig. 3 Fig. 4  
Inner pin and outer female body component group may be ordered in kit form, consisting of one each RCDX60-2, RMD26L-1, RCDXB-055-1 and YOC-074.  
Kit Catalog Number: RCDXK-1.

Coaxial Cable*	Contact For Inner Conductor				Contact For Outer Braid						Extraction Tool
	Pin Catalog Number	Fig. No.	Crimp Tool M10S-1		Outer Female Body		HYRING		Crimp Tool M10S-1		
			Die Set	Stop Bushing	Catalog Number	Fig. No.	Catalog Number	Fig. No.	Die Set	Stop Bushing	
RG161/U RG179A/U RG187/U	RMD26L-1	1	S-23	SL-46	RCDX60-2		YOC-074	3	S-22	SL-47	RX20-25 or RXK20-25
RG174/U RG188/U Amphenol 21-598	RMD26L-1		S-26	SL-46	RCDX60-2	2	YOC-074	3	S-22	SL-47	RX20-25 or RXK20-25
RG178A/U RG196/U	RMD26L-1		S-23	SL-46	RCDX60-2		YOC-074 RCDXB055-1	3 4	S-22	SL-47	RX20-25 or RXK20-25

\*Wire types other than those noted may also be accommodated by contacts above. Refer to Burndy, giving wire particulars.




Fig. 1 Fig. 2 Fig. 3 Fig. 4  
Inner socket and outer male body component group may be ordered in a kit form, consisting of one each RMDX60-2, RFD26L-1, RMDXB-055-1, YOC-074.  
Kit Catalog Number: RMDXK-1.

Coaxial Cable*	Contact For Inner Conductor				Contact For Outer Braid						Extraction Tool
	Socket Catalog Number	Fig. No.	Crimp Tool M10S-1		Outer Male Body		HYRING		Crimp Tool M10S-1		
			Die Set	Stop Bushing	Catalog Number	Fig. No.	Catalog Number	Fig. No.	Die Set	Stop Bushing	
RG161/U RG179A/U RG187/U	RFD26L-1	1	S-23	SL-46	RMDX60-2		YOC-074	3	S-22	SL-47	RX20-25 or RXK20-25
RG174/U RG188/U Amphenol 21-598	RFD26L-1		S-26	SL-46	RMDX60-2	2	YOC-074	3	S-22	SL-47	RX20-25 or RXK20-25
RG178A/U RG196/U	RFD26L-1		S-23	SL-46	RMDX60-2		YOC-074 RMDXB055-1	3 4	S-22	SL-47	RX20-25 or RXK20-25

\*Wire types other than those noted may also be accommodated by contacts above. Refer to Burndy, giving wire particulars.

Subminiature Coaxial Contacts for Twisted Pair

An additional application of the newly designed subminiature coaxial contacts, type RMDX/RCDX-2, is their use with the twisted pair. Two twisted no. 26 or no. 24 solid or stranded wires, are accommodated by the contact, using an auxiliary supporting sleeve Type YORX. In-



stallation tooling for assembling the twisted pair is identical to standard tooling for subminiature coaxial cable applications. However, a secondary crimp has been added to the outer HYRING to secure the auxiliary supporting sleeve, thus providing additional mechanical strength.

## No. 16 (.0625 dia.) MACHINED CONTACTS type RM/RC-M

The .0625 diameter machined HYFEN pins and sockets, which accommodate no. 26 thru no. 16 wires are recommended for Military and high reliability applications. Barrels on both contacts usually have an insulation grip to support the wires against bending and vibration stresses. They also have a cable stop and inspection hole to assure perfect crimps every time.

These contacts meet the applicable performance requirements and crimp joint characteristics

of MIL-C-22857, and will mate and are interchangeable with the no. 16 (.0625) diameter formed contacts, type SM/SC-M.

Contacts with the prefix M- are furnished in expendable plastic carry strips for semi-automatic installation with the YD2-1 HYPRESS.

Wire sizes other than those shown may also be accommodated; refer to BURNDY giving wire particulars.

### Performance characteristics

Current rating 13 amperes

Contact voltage drop 23 millivolts at 13 amperes

Contact retention 25 pounds

Wire Size and Mil. Spec.	Cable Strip Length	Pin Contact		Socket Contact		Crimping Tools					Extraction Tool Cat. No.
		Catalog Number	Fig.	Catalog Number	Fig.	M8ND/Y8ND "N" Die Set Cat. No.	YD2-1 Die Set Cat. No.	M10S-1 Die Set Cat. No.	Stop Bushing	Bandomatic (Type AM2-2) Die Set Cat. No.	
26 str., MIL-W-16878C type B, E, EE; 24 str., MIL-W-16878C type B, C, E, EE, F	.188	RM24M-9 M-RM24M-9 C-RM24M-9	1	RC24M-9 M-RC24M-9 C-RC24M-9	4	N24RT-10 — —	— YDD83-1 —	S-9 — —	SL-40 — —	— — AMK-4	RX20-25 or RXK20-25
22 str., MIL-W-16878C type B, EE, F; MIL-W-5086A type T 20 str., MIL-W-16878C type B, E	.188	RM20M-13 M-RM20M-13 C-RM20M-13	2	RC20M-13 M-RC20M-13 C-RC20M-13	5	N20RT-30 — —	— YDD82-1 —	S-10 — —	SL-40 — —	— — AMK-6	RX20-25 or RXK20-25
22 str., MIL-W-16878C type C; MIL-W-5086A type II, III; MIL-W-76A type MW 20 str., MIL-W-16878C type C, EE, F; MIL-W-5086A type I, II; MIL-W-76A type MW	.188	RM20M-12 M-RM20M-12 C-RM20M-12	2	RC20M-12 M-RC20M-12 C-RC20M-12	5	N20RT-30 — —	— YDD82-1 —	S-10 — —	SL-40 — —	— — AMK-6	RX20-25 or RXK20-25
20-16 str. MIL-W-16878C type B, C, E, EE, F, J, K, KK; MIL-W-5086A type I, II, III; MIL-W-76A type MW	.188	RM16M-23 M-RM16M-23 C-RM16M-23	3	RC16M-23 M-RC16M-23 C-RC16M-23	6	N16RT-21 — —	— YDD81-1 —	S-3 — —	SL-39 — —	— — AMK-10	RX20-25 or RXK20-25




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

## No. 16 (.0625 dia.) FORMED CONTACTS type SM/SC-M

The .0625 diameter formed HYFEN pins and sockets have been designed to provide reliability with economy. Supplied 3000 contacts to a reel — on a continuous strip for high speed, low cost, fully-automatic installation; the contacts can be cut from the strip for individual hand tool installation. These contacts accept no. 26 thru no. 20 solid and stranded wires, and have insulation grips to support wires against

bending and vibration stresses.

The crimped connection meets the applicable performance characteristics of MIL-T-7928 and are recommended for high volume applications or where low cost is emphasized. They will mate and are interchangeable with the no. 16 (.0625) diameter machined contacts, type RM/RC-M.

Connectors assembled with either type

no. 16 HYFEN contacts will mate with existing solder or crimp type connectors having .0625 diameter contacts.

### Performance characteristics


Current rating 13 amperes

Contact voltage drop 25 millivolts at 13 amperes


Contact retention 15 pounds

Wire Size and Mil. Spec.	Cable Strip Length	Pin Contact			Socket Contact			Contact Crimping Tools		Extraction Tool Cat. No.
		Catalog Number*	Dimensions in Inches		Catalog Number*	Dimensions in Inches		M8ND/Y8ND "N" Die Set Cat. No.	HYFEMATIC Die Set Cat. No.	
			L	OD		L	OD			
26-24 sol. and str. MIL-W-16878C type B, C, E, EE, F; MIL-W-76A type LW, MW	.188	SM24M-1	1.05	.128	SC24M-1	.71	.128	N24RT-11	DM5-1	RX20-25 or RXK20-25
22-20 sol. and str. MIL-W-16878C type B, C, E, EE, F; MIL-W-5086 type I; MIL-W-76A type LW, MW	.188	SM20M-1	1.05	.139	SC20M-1	.71	.139	N20RT-29	DM5-1	RX20-25 or RXK20-25

\*Wire types other than those noted may also be accommodated by contacts above. Refer to Burndy, giving wire particulars.



pin




socket



# TRIM TRIO CONNECTORS

A variety of connectors for broad application are available to accommodate any combination of the TRIM TRIO contacts.



**Miniature  
Rectangular HYFEN® Connector  
type MS-M**


This connector is offered in a complete range of 14, 20, 26, 34, 42, 50, and 75 contact positions. The plug (MS-PM) and receptacle (MS-RM) of this line of connectors will accept any combination of no. 16 (.0625) diameter machined, formed, and subminiature coaxial contacts.

Plugs and receptacles are molded of glass-filled phenolic (MIL-M-14F Type MFH) and can also be furnished in glass-filled diallyl phthalate (MIL-M-19833, Type GDI-30).

BURNDY MS-M type connectors meet or exceed the applicable performance requirements of MIL-C-8384, MIL-C-22857, MIL-T-7928, and MIL-F-21608.


A full line of accessories—hoods, jackscrews, and polarizing guide pins—are available for use with MS-M HYFEN connectors. For detailed information see the BURNDY Rack and Panel Catalog RP.

A .104 position connector incorporating a center jackscrew is also available.



**Sub-miniature Coax Cable Splice Connector type RSMDEX-1/RSCDEX-1**

The sub-miniature coax cable splice connector offers a quick connect-disconnect, snap-lock splice for the TRIM TRIO contacts. The plug (RSCDEX-1) will accept the no. 16 sockets and the outer female sub-miniature coaxial contacts (RMDXK-2), while the receptacle (RSMDEX-1) will accept the no. 16 pins and outer male sub-miniature coaxial contacts (RCDXK-2). Plugs and receptacles are molded of nylon.




**High Density Connector  
type MB-152**

For rack and panel application, this connector enables the designer to accommodate 152 contacts into one single unit. The plug will accept any combination of the no. 16 sockets and the RCDXK-2 subminiature coaxial male contact assemblies. The receptacle will accept any combination of the no. 16 machined or formed pins and the RMDXK-2 subminiature coaxial female contact assemblies. Plugs and receptacles are molded of glass-filled phenolic (MIL-M-14F, Type MFH).

These connectors mate and are completely interchangeable with other existing crimp and solder type connectors.

Non-reversible pin and socket polarizing guides and jackscrews prevent misalignment and mismatching. A center jackscrew provides ease of connecting and disconnecting while maintaining positive engagement through severe environmental stresses.

The MB152 connector meets the applicable performance requirements of MIL-C-22857, MIL-T-7928, and MIL-F-21608.



**HYFEN AQUALOK® Connector  
type MA28C97**


The quick disconnect, environmentally sealed unit with a high density configuration accommodates 55 contacts per connector, and will accept any combination of TRIM TRIO no. 16 machined, formed and subminiature coaxial contacts. This cylindrical connector is similar to MIL-C-5015 type connectors and conforms to the applicable portions of this specification and MIL-C-26482.

The inserts are made of glass-filled diallyl phthalate (MIL-M-19833, Type GDI-30F) and have a variety of four possible polarizing positions to avoid mismatching where more than one set of connectors is used.

The plug and receptacle can be ordered to accept either pins or sockets. A modified, double stub threaded coupling on the shell hardware ensures full mating of the connectors and also provides a method for rapid quick disconnect of the mating halves.

Protective caps are available to seal the connectors when unmated, for both the plug and receptacle. They are attached to the connectors or jacketed cable adaptors by a continuous weave stainless steel wire rope for flexibility and mechanical strength.

Consult BURNDY for details and ordering instructions on AQUALOK connectors.



**Modular HYFEN Connector  
type PD57**

Having high density configuration, this module will accept any combination of the TRIM TRIO contacts up to 57 positions. It will fit into any available PD-H frames for 3, 5, 8, 12 inserts in multiples or in combination with the other PD type inserts. The plug (PD57M-1) is normally used with any combination of no. 16 pins and the female subminiature coaxial contacts (RMDXK-2), while the receptacle is used with no. 16 sockets and male subminiature coaxial contacts (RCDXK-2). The plug or receptacle however, will accept either pins or sockets.

The connector is made of high dielectric strength, glass-filled phenolic (MIL-M-14F, Type MFH). A tin-plated beryllium copper shield on the receptacle grounds it to the frame, and polarized guide pins engage before the contacts. Jackscrews on both ends fasten the plug to the frame, providing the necessary engaging forces.

PD57 modular HYFEN connectors meet the applicable performance requirements of MIL-C-22857, MIL-T-7928, and MIL-F-21608.



# Installation Tooling

All tooling is full cycling, thereby guaranteeing a complete crimp each time a tool is activated, providing a built-in quality control.




## M10S-1 HYTOOL®

With removable die sets, designed to conform to the requirements of MIL-T-22520. Four-indent die sets install variety of Burndy contacts. Die sets can include insulation grip feature.



## M8ND and Y8ND

These companion tools have removable dies which are interchangeable for easy change-over from prototype to mass production.



## YD2-1 HYPRESS®

High production, semi-automatic, pneumatic, magazine-load tool. Contacts are supplied in expendable plastic carry strips for quick loading. Can be operated as hand tool, or bench-mounted.

## BANDOMATIC®

Installs a wide variety of contacts, 3000 per hour. Easy loading. Simple die changes enhance versatility. Crimped contacts conform to the applicable areas of MIL-T-22520 and MIL-T-7928.



## HYFEMATIC®

Automatically installs strip-fed contacts. High production rates, up to 4000 per hour. Installs contacts for Burndy's .078", .100", and .156" spacing EDGE-ON connectors.



## RX20-25

Extraction Tool Has a spring loaded steel outer sleeve that depresses contact locking spring and an inner plunger that pushes out contact.



## RXK20-25

Extraction Tool Has a fixed outer sleeve that depresses contact locking spring. With tool still in contact hole, remove contact by pulling it out from back end of connector.

# BURNDY


Norwalk, Connect.





# BURNDY TRIM TRIO

A new and unique approach in contact design is offered with the BURNDY TRIM TRIO. Any of the three; the subminiature coax, the machined, and the formed contacts, can be used in any combination in the positions of the connectors shown in this brochure.



The TRIM TRIO enables the user to make solid and stranded wire or subminiature coax cable installations at the most convenient point in his production cycle. The contacts can be easily inserted, removed and reinserted for circuit changes and checks. The versatility and economy of this family of contacts and connectors merit first consideration on any new project or standardization program, where simplification of manufacturing problems are combined with reducing costs.

**FOR INFORMATION AND SERVICE...**

## **CONTACT YOUR BURNDY REPRESENTATIVE**

**BALTIMORE, MARYLAND 21206**

**BOSTON, MASS.**

**BUFFALO, N. Y. 14203**

**CEDAR RAPIDS, IOWA 52405**

**CHARLESTON, WEST VIRGINIA 25304**

**CHARLOTTE, N. C. 28204**

**CHICAGO, ILLINOIS**

**CINCINNATI, OHIO 45227**

**CLEVELAND, OHIO 44134**

**DALLAS, TEXAS 75203**

**DENVER, COLORADO 80205**

**DES MOINES, IOWA 50310**

**DETROIT, MICHIGAN**

**HONOLULU, HAWAII 96809**

**HOUSTON, TEXAS 77004**

**HUNTSVILLE, ALA. 35805**

**JACKSON, MISS. 39205**

**KANSAS CITY, MO.**

**LITTLE ROCK, ARK. 72203**

**LOS ANGELES, CALIF.**

**MEMPHIS, TENN.**

**NEW ORLEANS, LA. 70125**

**NEW YORK OFFICE**

**NORWALK, CONN. 06852**

**ORLANDO, FLORIDA 32804**

**PHILADELPHIA, PA.**

**PHOENIX, ARIZONA 85017**

**PITTSBURGH, PA. 15237**

**RICHMOND, VA. 23219**

**ST. LOUIS, MO. 63131**

**ST. PAUL, MINN. 55104**

**SAN FRANCISCO, CALIF.**

**SEATTLE, WASH. 98144**

**SHREVEPORT, LA. 71101**

**SYRACUSE (East) N. Y. 13206**

**WASHINGTON, D. C. 20013**

BRADLEY ELECTRO SALES CORP., 4132 Mary Ave., P. O. Box 6220 — 301-254-9129

BURNDY OF NEW ENGLAND INC., 31 Washington St., Wellesley Hills, Mass. 02181 — 617-235-8686

VINCENT J. BROWN CO., 564 Ellicott Square Bldg. — 716-TL 2-1122

BURNDY CORPORATION, Mr. Kenneth W. Horn, 1025 - 18th St., N. W. — 319-362-5669

PAUL A. SKAFF ENGINEERING CO., 3912 MacCorkle Ave., S. E., P. O. Box 4198 — 304-925-9876

GLENN A. LARSON OF CAROLINA, INC., 1321 E. Morehead St., P. O. Box 4375 — 704-ED 4-3994

BURNDY MIDWEST INC., 9420 River St., Schiller Park, Ill. 60176 — 312-678-5211

BURNDY OF OHIO INC., 5710 Wooster Pike — 513-272-0255

BURNDY OF OHIO INC., 3435 Brookpark Rd. — 216-749-5607

ELGIN B. ROBERTSON INC., 1339 Plowman St. — 214-WH 2-3157

BURNDY OF COLORADO INC., 4049 St. Paul St. — 303-377-8891

BURNDY CORP., 2731 Douglas Ave. — 515-274-3804

BURNDY OF MICHIGAN INC., 28630 Southfield Rd., Lathrup Village, Mich. 48037 — 313-444-1424

HONOLULU ELECTRICAL PRODUCTS CO. LTD., P. O. Box 459 — 581-111

ELGIN B. ROBERTSON, INC., 4101 San Jacinto — 713-JA 9-3797

BURNDY SOUTHEAST INC., 2109 West Clinton Bldg., Rm 326 — 205-536-511

CURTIS H. STOUT OF MISS. INC., 236 E. Capitol St. — 601-354-4326

PENZNER ASSOCIATES, INC., 6920 W. 82nd St., P. O. Box 4362, Overland Park, Kansas 66204 — 913-DU 1-0004

CURTIS H. STOUT, INC., 400 Shall St., P. O. Box 107 — 501-FR 4-8201

BURNDY OF CALIFORNIA INC., 1111 E. El Segundo Blvd., El Segundo, Calif. 90246 — 213-772-5401

CURTIS H. STOUT OF TENN. INC., 715 M & M Bldg. — 901-JA 6-7601

CURTIS H. STOUT OF LOUISIANA, INC., 1420 S. Jefferson Davis Parkway — 504-861-4531

BURNDY CORP., 2 Penn Place, Pelham, N. Y. — PE 8-3200, NYC No. LU 4-9300

BURNDY CORP., Richards Ave. — 203-838-4444

BURNDY SOUTHEAST INC., 725 West Smith Ave. — 305-CH 1-1576

BURNDY OF PENNSYLVANIA INC., Box 56, King of Prussia, Penn. 19406 — 215-242-0600

BURNDY OF CALIFORNIA INC., 3918 North 30th Avenue — 602-264-2701

MULLER, HARPER & ASSOC. INC., 7805 McKnight Rd., P. O. Box 11147 — 412-931-6460

BRADLEY ELECTRO SALES CORP., Room 711, Southern States Bldg., 7th & Main St. — 703-648-9366

BURNDY OF MISSOURI INC., 13014 Manchester Rd. — 314-YO 6-8466

BURNDY OF MINNESOTA INC., 1821 University Ave. — 612-646-7293

BURNDY OF CALIFORNIA INC., 560 San Antonio Rd., Palo Alto, Calif. 94306 — 415-327-4410

BURNDY NORTHWEST INC., 1700 - 21st Avenue S. — 206-EA 5-1730

CURTIS H. STOUT, INC., 409 Fairfield Bldg. — 318-425-5485

VINCENT J. BROWN CO., 23 Eastern Ave., P. O. Box 142 Eastwood Station — 315-HO 3-9161

BRADLEY ELECTRO SALES CORP., 212 "H" Street, N. W. — 202-RE 7-1300

 **BURNDY**  
NORWALK, CONNECTICUT 06852